5

10

15

20

25

Section 2: Amendments to the Specification

In the specification, at page 6, beginning line 1:

Detailed Description of the Preferred Embodiments

Detailed descriptions of the preferred embodiment are provided herein. It is to be understood, however, that the present invention may be embodied in various forms. Therefore, specific details disclosed herein are not to be interpreted as limiting, but rather as a basis for the claims and as a representative basis for teaching one skilled in the art to employ the present invention in virtually any appropriately detailed system, structure or manner.

Referring now to Figure 1 we see a perspective view of the invention **100** shown attached to a standard baby stroller **13**. The invention **100** is comprised of a flexible screen portion **2**, a frame portion comprised of a cloth binding strip **4** and an internal spring steel band 40 shown in section view in Figure 6 and two pairs of hook and loop fastening strips **6**,**8**,**10**,**12**. The fastening strips **6**,**8**,**10**,**12** are sewn to each end of the frame **4** as shown in Figure 2. The screen **2** and frame **4** form an elongated ellipse of a sufficient width to extend from one side frame member of a standard baby carriage to the opposite side frame member.

{end paragraph}

approximately --- long and --- inches wide.

The screen **2** is made of flexible polyester plastic or other standard flexible screening material. The hook and loop fastening strips **6**, **8**, **10**, **12** are approximately two inches wide and six inches long. Each strip is sewn on one



end to binding cloth **4**. Screen **2** is sewn between the lips **30**, **32** of binding portion **4** as shown in Figure 6. The strips **6**,**8**, **10**, **12** are used to removably attach the frame **4** and enclosed screen **2** to the stroller frame **20** of a standard stroller **13** as shown in Figure 1. The shape of screen **2** and frame **4** is such that the top edge of frame 4 makes intimate contact with the leading edge of canopy **102** so that the screen 2 can protect the occupant of the stroller **13** from the uncomfortable and potentially damaging effects of full exposure to low angled sun. **{end paragraph}**